

Haitai TaiHe2.0 (182)

HTM565~585DMH5-72NT TOPCon Bifacial high efficiency PV module

22.65%

Module Efficiency 22.65%

PRODUCT FEATURES

High Power Output
N-type MBB half cut technology, improve energy density, bring higher power output.
High Bifacial Factor, up to 25% extra power generation

High Durability
Passed TUV Salt & Ammonia corrosion test, and 2400Pa wind load, 5400Pa snow load test, higher reliability


Better Low Light Performance
Higher power generation compare with standard module in cloudy, foggy and low light condition

Low Power Degradation
First year power degradation <1.0%, year 2-30 power degradation <0.40% each year

Low Temperature coefficient
Passivated contact cell technology for higher power generation in operating

Better Anti-LID
N-type cells with boron-oxide-free composite LID to increase module power generation

LINEAR PERFORMANCE WARRANTY



12 YEARS product warranty

30 YEARS linear power warranty

0.40% Linear attenuation of 0.40% per year within 30 years

CERTIFICATES

- IEC 61215, IEC 61730
- ISO 9001: 2015 Quality Management System
- ISO 14001: 2015 Environment Management System
- ISO 45001: 2018 Occupational health and safety management systems
- IEC62941:2019 Photovoltaic Module Manufacturer Quality Management System



Electrical Data (STC)

Maximum Power (Pmax/W)	565	570	575	580	585
Open Circuit Voltage (Voc/V)	51.74	51.89	52.04	52.19	52.34
Short Circuit Current (Isc/A)	13.65	13.73	13.81	13.89	13.97
Voltage at Maximum Power (Vmp/V)	43.46	43.61	43.76	43.91	44.06
Current at Maximum Power (Imp/A)	13.01	13.08	13.14	13.21	13.28
Module Efficiency (%)	21.87	22.07	22.26	22.45	22.65
Operating Temperature	-40° C~+85° C				
Maximum System Voltage	1000/1500V				
STC (Standard Testing Conditions): Irradiance 1000W/m ² , Cell Temperature 25°C, AM1.5					

Electrical Data (NMOT)

Maximum Power (Pmax/W)	425	429	433	437	441
Open Circuit Voltage (Voc/V)	49.14	49.29	49.44	49.59	49.72
Short Circuit Current (Isc/A)	11.16	11.23	11.30	11.37	11.45
Voltage at Maximum Power (Vmp/V)	40.39	40.54	40.69	40.84	40.92
Current at Maximum Power (Imp/A)	10.53	10.59	10.65	10.71	10.78

NMOT (Nominal Module Operating Temperature): Irradiance 800W/m², Ambient Temperature 20°C, AM1.5, Wind Speed 1m/s.

Bifacial Power Generation Parameters (Backside Gains)

5%	Maximum Power (Pmax/W)	593	599	604	609	614
	Module Efficiency (%)	22.97	23.17	23.37	23.57	23.78
15%	Maximum Power (Pmax/W)	650	656	661	667	673
	Module Efficiency (%)	25.15	25.37	25.60	25.82	26.04
25%	Maximum Power (Pmax/W)	706	713	719	725	731
	Module Efficiency (%)	27.34	27.58	27.82	28.07	28.31

Mechanical Data

Cell Type	182×91mm Mono
Cell Orientation	144(6×24)
Module Dimensions	2278×1134×30mm
Weight	32.0kg
Glass	2.0mm high transmittance, reinforced glass
Backsheet	2.0mm part of the structure is grid-like black ceramic glass
Frame Material	Anodized aluminum alloy(Black)
Junction Box	Protection class IP68
Cable	4.0 mm ² positive pole: 200 mm negative pole: 250 mm wire length can be customized
Connector	MC4 compatible connector


Temperature Coefficients

Temperature Coefficient (Pm)	-0.300%/°C
Temperature Coefficient (Voc)	-0.250%/°C
Temperature Coefficient (Isc)	0.046%/°C
NMOT (Nominal Module Operating Temperature)	41±3°C

Packaging

Transportation methods	Number of modules per cabinet	Number of modules per pallet
40HQ container	720 pcs	36 pcs +36 pcs

Module Dimensions (mm)



I-V Curve

